



- A 300×240×110 mm
- B 400×300×128 mm
- C 500×400×130 mm, see larger picture
- D 650×500×142 mm
- E 800×600×200 mm

- Cable length of display device approx. 3 m
- Permissible ambient temperature - 10 °C/40 °C

Platform scale in heavy version with EC type approval [M], now also up to [Max] 600 kg

Features

- **Tough industry standard** suitable for use in harsh industrial applications
- **1 Platform:** weighing plate stainless steel, painted steel base, silicone-coated aluminium load cell, protection against dust and water splashes IP65, Platform can also be delivered as component without the display device, for details see KERN KFP V20

- **Benchtop stand incl. wall mount** for display device as standard

Technical data

- Large backlit LCD display, digit height 52 mm
- Weighing plate dimensions, stainless steel W×D×H

Accessories

- **Protective working cover**, can be re-ordered, scope of delivery: 5 items, KERN KFB-A02S05
- **Rechargeable battery pack internal**, operating time up to 35 h, without backlight, charging time approx. 12 h, must be ordered at purchase, KERN KFB-A01
- **Stand** to elevate display device, for models with weighing plate size A, B: height of stand approx. 330 mm, KERN IFB-A01
C - E: 2 height of stand approx. 600 mm, KERN IFB-A02
A - D: height of stand approx. 800 mm, KERN BFS-A07
- Further details, plenty of further accessories and suitable printers see *Accessories*


STANDARD



OPTION











FACTORY



Model	Weighing range [Max] kg	Read-out [d] g	Verification value [e] g	Minimal load [Min] g	Net weight approx. kg	Weighing plate	Options			
							Verification		DAkkS Calibr. Certificate	
							M	KERN	DKD	KERN
IFB 6K-4	6	0,2	-	-	6	A	-	-	963-128	
IFB 10K-4	15	0,5	-	-	6	A	-	-	963-128	
IFB 10K-4L	15	0,5	-	-	10	B	-	-	963-128	
IFB 30K-3	30	1	-	-	10	B	-	-	963-128	
IFB 60K-3	60	2	-	-	10	B	-	-	963-129	
IFB 60K-3L	60	2	-	-	13	C	-	-	963-129	
IFB 100K-3	150	5	-	-	14	C	-	-	963-129	
IFB 100K-3L	150	5	-	-	22	D	-	-	963-129	
IFB 300K-2	300	10	-	-	20	D	-	-	963-129	
IFB 600K-2	600	20	-	-	46	E	-	-	963-130	
Dual-range balance switches automatically to the next largest weighing range [Max] and readout [d]										
IFB 6K1DM	3 6	1 2	1 2	20 40	6	A	965-228	-	963-128	-
IFB 15K2DM	6 15	2 5	2 5	40 100	6	A	965-228	-	963-128	-
IFB 15K2DLM	6 15	2 5	2 5	40 100	10	B	965-228	-	963-128	-
IFB 30K5DM	15 30	5 10	5 10	100 200	11	B	965-228	-	963-128	-
IFB 60K10DM	30 60	10 20	10 20	40 100	11	B	965-229	-	963-129	-
IFB 60K10DLM	30 60	10 20	10 20	200 400	13	C	965-229	-	963-129	-
IFB 150K20DM	60 150	20 50	20 50	400 1000	14	C	965-229	-	963-129	-
IFB 150K20DLM	60 150	20 50	20 50	400 1000	20	D	965-229	-	963-129	-
IFB 300K50DM	150 300	50 100	50 100	1000 2000	22	D	965-229	-	963-129	-
IFB 600K1M	300 600	100 200	100 200	2000 4000	46	E	965-230	-	963-130	-

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

KERN Pictograms:

 CAL INT	Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motodriven).	 PCS	Piece counting : Reference quantities selectable. Display can be switched from piece to weight	 ACCU	Rechargeable battery pack : Rechargeable set
 CAL EXT	Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.	 RECIPE A	Recipe level A : Separate memory for the weight of the tare container and the recipe ingredients (net total).	 MULTI	Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 MEMORY	Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 RECIPE B	Recipe level B : Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 230 V	Mains adapter : 230V/50Hz in standard version for EU. On request GB, USA or AUS version available
 ALIBI	Alibi memory: Electronic archiving of weighing results, complying with the 2014/31/EU standard.	 RECIPE C	Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition.	 230 V	Power supply : Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.
 RS 232	Data interface RS-232 : To connect the balance to a printer, PC or network.	 SUM	Totalising level A: The weights of similar items can be added together and the total can be printed out.	 DMS	Weighing principle: Strain gauge Electrical resistor on an elastic deforming body
 RS 485	RS-485 data interface : To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 PERCENT	Percentage determination : Determining the deviation in % from the target value (100 %).	 T-FORK	Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate.
 USB	USB data interface : To connect the balance to a printer, PC or other peripherals.	 UNIT	Weighing units : Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 FORCE	Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
 BT	Bluetooth* data interface : To transfer data from the balance to a printer, PC or other peripherals.	 TOL	Weighing with tolerance range : Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning	 SC TECH	Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision
 WLAN	WLAN data interface : To transfer data from the balance to a printer, PC or other peripherals.	 MOVE	Hold function : (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 M +3 DAYS	Verification possible : The time required for verification is specified in the pictogram.
 SWITCH	Control outputs (optocoupler, digital I/O) : To connect relays, signal lamps, valves, etc.	 IP	Protection against dust and water splashes IPxx : The type of protection is shown in the pictogram.	 DAKKS +3 DAYS	DAkkS calibration possible (DKD) : The time required for DAkkS calibration is shown in days in the pictogram
 DUAL	Interface for second balance : For direct connection of a second balance	 ATEX	ATEX explosion protection : Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device	 1 DAY	Package shipment : The time required for internal shipping preparations is shown in days in the pictogram
 LAN	Network interface : For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 INOX	Stainless steel : The balance is protected against corrosion.	 2 DAYS	Pallet shipment : The time required for internal shipping preparations is shown in days in the pictogram.
 RC	Wireless data transfer : between the weighing unit and the evaluation unit using an integrated radio module.	 3 YEARS WARRANTY	Warranty : The warranty period is shown in the pictogram		
 GLP INTERN	GLP/ISO log : The balance displays the weight, date and time, regardless of a printer connection.	 UNDER	Suspended weighing : Load support with hook on the underside of the balance		
 GLP PRINTER	GLP/ISO log : With weight, date and time. Only with KERN printers.	 BATT	Battery operation : Ready for battery operation. The battery type is specified for each device		

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

Impex Produkter AS
Gamle Drammensvei 107
1363 HØVIK
Tel. 22 32 77 20
info@impex.no
www.impex.no