

# Hanging scales KERN HCB · HCN



KERN HCB



KERN HCN



## The handy scales for higher loads up to 1 t

### Features

- With the **TÜV certification mark**, the scale meets the requirements of the standard EN 13155 (Non-fixed load lifting attachments/Breakage resistance) and EN 61010-1 (Electrical safety)
- Ideal for rapid control in goods-in and goods-out
- Also essential in the private sector to determine the weight of fish, game, fruits, bicycle parts, suitcases etc.
- Hold function:** For easy reading of the weighing result, the display can be „frozen“ in different ways. Either automatically when the weighing value remains unchanged or manually by pressing the Hold key
- Peak load display** (peak hold), measuring frequency 5 Hz

### Technical data

- LCD display, digit height 12 mm
- Hole diameter of load support, model with [Max] ≤ 200 kg: approx. 14 mm  
[Max] > 200 kg: approx. 16 mm

### HCB

- Ready for use: Batteries included, 3×1.5 V AA, operating time up to 300 h
- [Max] ≥ 0,5 t: Reinforced version for heavy loads. Snap link and Hook not included

### HCN

- Housing stainless steel, protected against dust and water splashes IP65
- Second display** on the rear of the balance
- Ready for use: Batteries included, 3×1.5 V AA, operating time up to 300 h

### Accessories

#### for models with [Max] ≤ 200 kg

- Snap link** (stainless steel) with safety catch, standard, opening approx. 15 mm. Can be retrofitted, KERN HCB-A01
- Hook** (stainless steel), standard, opening approx. 25 mm. Can be reordered, KERN HCB-A02

#### for models with [Max] ≤ 20 kg

- Tare pan with pan beam**, details see *Accessories*, KERN CH-A01N

#### for models with [Max] ≥ 0,5 t

- Hook with safety lock**, cast steel, galvanised and coated, with stud bolt, non-rotating, suitable for models KERN HCB, HFA, HFC with [Max] ≤ 1 t, KERN YHA-01
- High-strength shackle**, cast steel, hot-dip galvanised, bow shaped with coated stud bolt, suitable for models KERN HCB, HFA, HFC with [Max] ≥ 0,5 t, KERN YSC-03

### STANDARD










































### OPTION



Model	Weighing range	Readout	Dimensions housing W×D×H mm	Height with hook and snap link mm	Net weight ca. kg	Option	
						DAkks Calibr. Certificate	
KERN	[Max] kg	[d] g				DKD KERN	
HCB 20K10	20	10	80×45×150	290	0,60	963-128H	
HCB 50K20	50	20	80×45×150	290	0,60	963-128H	
HCB 50K100	50	100	80×45×150	290	0,60	963-128H	
HCB 99K50	99	50	80×45×150	290	0,60	963-129H	
HCB 100K200	100	200	80×45×150	290	0,35	963-129H	
HCB 200K100	200	100	80×45×150	290	0,60	963-129H	
HCB 200K500	200	500	80×45×150	290	0,60	963-129H	
HCB 0.5T-3	500	1000	80×42×152	-	0,35	963-130H	
HCB 1T-3	1000	2000	80×48×150	-	0,55	963-130H	
Stainless steel							
HCN 50K100IP	50	100	95×50×180	315	0,80	963-128H	
HCN 100K200IP	100	200	95×50×180	315	0,80	963-129H	
HCN 200K500IP	200	500	95×50×180	315	0,80	963-129H	

# KERN Pictograms:

 Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motodriven).	 Piece counting : Reference quantities selectable. Display can be switched from piece to weight	 Rechargeable battery pack : Rechargeable set
 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.	 Recipe level A : Separate memory for the weight of the tare container and the recipe ingredients (net total).	 Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 Recipe level B : Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 Mains adapter : 230V/50Hz in standard version for EU. On request GB, USA or AUS version available
 Alibi memory: Electronic archiving of weighing results, complying with the 2014/31/EU standard.	 Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition.	 Power supply : Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.
 Data interface RS-232 : To connect the balance to a printer, PC or network.	 Totalising level A: The weights of similar items can be added together and the total can be printed out.	 Weighing principle: Strain gauge Electrical resistor on an elastic deforming body
 RS-485 data interface : To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 Percentage determination : Determining the deviation in % from the target value (100 %).	 Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate.
 USB data interface : To connect the balance to a printer, PC or other peripherals.	 Weighing units : Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
 Bluetooth* data interface : To transfer data from the balance to a printer, PC or other peripherals.	 Weighing with tolerance range : Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning	 Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision
 WLAN data interface : To transfer data from the balance to a printer, PC or other peripherals.	 Hold function : (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 Verification possible : The time required for verification is specified in the pictogram.
 Control outputs (optocoupler, digital I/O) : To connect relays, signal lamps, valves, etc.	 Protection against dust and water splashes IPxx : The type of protection is shown in the pictogram.	 DAKKS calibration possible (DKD) : The time required for DAKKS calibration is shown in days in the pictogram
 Interface for second balance : For direct connection of a second balance	 ATEX explosion protection : Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device	 Package shipment : The time required for internal shipping preparations is shown in days in the pictogram
 Network interface : For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 Stainless steel : The balance is protected against corrosion.	 Pallet shipment : The time required for internal shipping preparations is shown in days in the pictogram.
 Wireless data transfer : between the weighing unit and the evaluation unit using an integrated radio module.	 GLP/ISO log : The balance displays the weight, date and time, regardless of a printer connection.	 Warranty : The warranty period is shown in the pictogram
 GLP/ISO log : With weight, date and time. Only with KERN printers.	 Suspended weighing : Load support with hook on the underside of the balance	
	 Battery operation : Ready for battery operation. The battery type is specified for each device	

## KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKKS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKKS calibration laboratory today is one of the most modern and best-equipped DAKKS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKKS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKKS calibration of balances with a maximum load of up to 50 t
- DAKKS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKKS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

## Your KERN specialist dealer:

Impex Produkter AS  
Gamle Drammensvei 107  
1363 HØVIK  
Tel. 22 32 77 20  
info@impex.no  
www.impex.no