



Ideal for food industry, thanks to its IP65 protection and special checkweighing display, now also with EC type approval [M]

Features

- Suitable for the ever-increasing hygienic requirements in the food industry
- Your support in a **HACCP**-compliant quality system
- **1** protection against dust and water splashes IP65 (only when using rechargeable battery pack)
- **Very fast display:** steady weight values within 2 s
- **2** **Second display** on the rear of the balance
- **Compact size**, practical for small spaces
- **3** **Innovative weighing with tolerance range (Checkweighing):** The colour of the display changes depending on the weight (too light/ok/too heavy) and is an aid to help with portioning, dosing and grading

- **High mobility:** thanks to rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations
- **Recessed grips on the underside** of the scale for easy transportation

Technical data

- Large backlit LCD display, digit height 25 mm
- Weighing plate dimensions, stainless steel, W×D×H 260×200×16,2 mm
- Overall dimensions W×D×H 285×315×128 mm
- Net weight approx. 3,2 kg
- Permissible ambient temperature -10 °C/40 °C

Accessories

- **Protective working cover**, standard, can be re-ordered, scope of delivery: 5 items, KERN RFB-A01S05
- **Rechargeable battery pack internal**, operating time up to 50 h without backlight, charging time approx. 12 h, KERN WTB-A01N
- **4** **Tare pan made of stainless steel**, ideal for weighing loose small parts, fruit, vegetables etc., W×D×H 370×240×20 mm, KERN RFS-A02
- Sturdy transport case to protect and store the scale, dimensions W×D×H 510×360×220 mm, KERN RFB-A02

STANDARD OPTION FACTORY




--	--	--	--	--	--	--	--	--	--	--

Model	Weighing range [Max] kg	Readout [d] g	Verification value g	Minimal load [Min] g	Options		
					Verification		DAkkS Calibr. Certificate
					KERN	KERN	DKD KERN
WTB 1K-4N	1,5	0,2	-	-	-	963-127	
WTB 3K-4N	3	0,5	-	-	-	963-127	
WTB 6K-3N	6	1	-	-	-	963-128	
WTB 10K-3N	15	2	-	-	-	963-128	
WTB 30K-3N	30	5	-	-	-	963-128	

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.

WTB 1K-4NM	1,5	0,5	0,5	10	965-227	963-127
WTB 3K-3NM	3	1	1	20	965-227	963-127
WTB 6K-3NM	6	2	2	40	965-228	963-128
WTB 10K-3NM	15	5	5	100	965-228	963-128
WTB 30K-2NM	30	10	10	200	965-228	963-128

KERN Pictograms:

 Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motodriven).	 Piece counting : Reference quantities selectable. Display can be switched from piece to weight	 Rechargeable battery pack : Rechargeable set
 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.	 Recipe level A : Separate memory for the weight of the tare container and the recipe ingredients (net total).	 Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 Recipe level B : Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 Mains adapter : 230V/50Hz in standard version for EU. On request GB, USA or AUS version available
 Alibi memory: Electronic archiving of weighing results, complying with the 2014/31/EU standard.	 Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition.	 Power supply : Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.
 Data interface RS-232 : To connect the balance to a printer, PC or network.	 Totalising level A: The weights of similar items can be added together and the total can be printed out.	 Weighing principle: Strain gauge Electrical resistor on an elastic deforming body
 RS-485 data interface : To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 Percentage determination : Determining the deviation in % from the target value (100 %).	 Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate.
 USB data interface : To connect the balance to a printer, PC or other peripherals.	 Weighing units : Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
 Bluetooth* data interface : To transfer data from the balance to a printer, PC or other peripherals.	 Weighing with tolerance range : Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning	 Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision
 WLAN data interface : To transfer data from the balance to a printer, PC or other peripherals.	 Hold function : (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 Verification possible : The time required for verification is specified in the pictogram.
 Control outputs (optocoupler, digital I/O) : To connect relays, signal lamps, valves, etc.	 Protection against dust and water splashes IPxx : The type of protection is shown in the pictogram.	 DAKkS calibration possible (DKD) : The time required for DAKkS calibration is shown in days in the pictogram
 Interface for second balance : For direct connection of a second balance	 ATEX explosion protection : Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device	 Package shipment : The time required for internal shipping preparations is shown in days in the pictogram
 Network interface : For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 Stainless steel : The balance is protected against corrosion.	 Pallet shipment : The time required for internal shipping preparations is shown in days in the pictogram.
 Wireless data transfer : between the weighing unit and the evaluation unit using an integrated radio module.	 GLP/ISO log : The balance displays the weight, date and time, regardless of a printer connection.	 Warranty : The warranty period is shown in the pictogram
 GLP/ISO log : With weight, date and time. Only with KERN printers.	 Suspended weighing : Load support with hook on the underside of the balance	
	 Battery operation : Ready for battery operation. The battery type is specified for each device	

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

Impex Produkter AS
Gamle Drammensvei 107
1363 HØVIK
Tel. 22 32 77 20
info@impex.no
www.impex.no