



**Note:** Official verification duty for commercial trade

Entry level model into professional counting, also with EC type approval [M], counting resolution of 30,000 points

**Features**

- **Precise counting:** The automatic reference weight optimisation of reference weight gradually improves the average piece weight value
- **Programmable using numerical key pad:**
  - required reference quantity
  - known reference weight
- **Three displays** for weight display (verifiable), reference weight, total weight
- **Audible Fill-to-target:** target quantity or target weight can be programmed. When the target value is reached, a signal will sound
- **Counting results memory:** adds up all individual piece counts, result is shown in total weight and total pieces

- **Energy management:** Backlight turns off after 5 sec
- **PRE-TARE function** for manual subtraction of a known container weight, useful for checking fill-levels
- **Two balances in one:** Changes from counting mode to weighing mode at the touch of a key

- Rechargeable battery pack internal, operating time up to 200 h without backlight, charging time approx. 8 h
- Net weight approx. 4,0 kg
- Permissible ambient temperature -10 °C/40 °C

**Technical data**

- Large backlit LCD displays, digit height 18 mm
- Dimensions weighing surface, stainless steel, WxD 300x225 mm
- Dimensions housing WxDxH 300x330x110 mm

**Accessories**

- **Protective working cover,** can be re-ordered, scope of delivery: 5 items, KERN CXB-A01S05
- **Rechargeable battery pack internal,** operating time up to 200 h without backlight, charging time approx. 8 h, KERN GAB-A04

STANDARD


CAL EXT PCS SUM ACCU 230 V DMS 1 DAY 2 YEARS WARRANTY

OPTION FACTORY

DAkkS +3 DAYS M +3 DAYS CXB-NM

Model	Weighing range [Max] kg	Readout [d] g	Verification value [e] g	Minimal load [Min] g	Smallest part weight [counting] g/piece	Counting resolution Points	Options			
							Verification		DAkkS Calibr. Certificate	
KERN							M KERN		DKD KERN	
CXB 3K0.2	3	0,2	-	-	0,1	30.000	-		963-127	
CXB 6K0.5	6	0,5	-	-	0,2	30.000	-		963-128	
CXB 15K1	15	1	-	-	0,5	30.000	-		963-128	
CXB 30K2	30	2	-	-	1	30.000	-		963-128	
Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible. Verification at the factory, we need to know the full address of the location of use.										
CXB 3K1NM	3	1	1	20	0,1	30.000	965-227		963-127	
CXB 6K2NM	6	2	2	40	0,2	30.000	965-228		963-128	
CXB 15K5NM	15	5	5	100	0,5	30.000	965-228		963-128	
CXB 30K10NM	30	10	10	200	1	30.000	965-228		963-128	

# KERN Pictograms:

 Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motodriven).	 Piece counting : Reference quantities selectable. Display can be switched from piece to weight	 Rechargeable battery pack : Rechargeable set
 Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required.	 Recipe level A : Separate memory for the weight of the tare container and the recipe ingredients (net total).	 Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 Recipe level B : Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 Mains adapter : 230V/50Hz in standard version for EU. On request GB, USA or AUS version available
 Alibi memory: Electronic archiving of weighing results, complying with the 2014/31/EU standard.	 Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition.	 Power supply : Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.
 Data interface RS-232 : To connect the balance to a printer, PC or network.	 Totalising level A: The weights of similar items can be added together and the total can be printed out.	 Weighing principle: Strain gauge Electrical resistor on an elastic deforming body
 RS-485 data interface : To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 Percentage determination : Determining the deviation in % from the target value (100 %).	 Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate.
 USB data interface : To connect the balance to a printer, PC or other peripherals.	 Weighing units : Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
 Bluetooth* data interface : To transfer data from the balance to a printer, PC or other peripherals.	 Weighing with tolerance range : Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning	 Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision
 WLAN data interface : To transfer data from the balance to a printer, PC or other peripherals.	 Hold function : (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 Verification possible : The time required for verification is specified in the pictogram.
 Control outputs (optocoupler, digital I/O) : To connect relays, signal lamps, valves, etc.	 Protection against dust and water splashes IPxx : The type of protection is shown in the pictogram.	 DAKkS calibration possible (DKD) : The time required for DAKkS calibration is shown in days in the pictogram
 Interface for second balance : For direct connection of a second balance	 ATEX explosion protection : Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device	 Package shipment : The time required for internal shipping preparations is shown in days in the pictogram
 Network interface : For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 Stainless steel : The balance is protected against corrosion.	 Pallet shipment : The time required for internal shipping preparations is shown in days in the pictogram.
 Wireless data transfer : between the weighing unit and the evaluation unit using an integrated radio module.	 GLP/ISO log : The balance displays the weight, date and time, regardless of a printer connection.	 Warranty : The warranty period is shown in the pictogram
 GLP/ISO log : With weight, date and time. Only with KERN printers.	 Suspended weighing : Load support with hook on the underside of the balance	
	 Battery operation : Ready for battery operation. The battery type is specified for each device	

## KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

## Your KERN specialist dealer:

**Impex Produkter AS**  
**Verkseier Furulunds vei 15**  
**0668 OSLO**  
**Tel. 22 32 77 20**  
**Fax 22 32 77 25**  
**info@impex.no**  
**www.impex.no**