



The bestsellers in parcel- and veterinary scales, also with XL-platform, and big weighing ranges

Features

- **Weighing plate stainless steel**, painted steel base
- **Simple and convenient 4-key operation**
- **Wall mount** for display device, standard
- **Hold function:** When the weighing conditions are unstable, a stable weight is calculated determining an average value
- KERN EOS: The scale can be easily transported using **rollers** and a **handle** and does not require much storage space
- **Protective working cover** included with delivery
- KERN EOS: **Non-slip rubber mat** included with delivery

Technical data

- Large LCD display, digit height 25 mm
- Weighing plate dimensions W×D×H
 - A** 315×305×55 mm
 - B** 550×550×75 mm, see larger picture
 - C** 550×550×75 mm
 - D** 900×550×60 mm
- Dimensions of display device W×D×H 215×110×50 mm
- Cable length of display device approx. 2 m
- Optional battery operation, 6×1.5 V AA not included, operating time up to 60 h
- Permissible ambient temperature 10 °C/35 °C

Accessories

- **Protective working cover** over the display device, scope of delivery: 5 items, KERN EOB-A02S05
- **1 Stand** to elevate display device, height of stand approx. 950 mm, can be retrofitted, KERN MWS-A01
- **2 KERN EOB: Stand** to elevate display device, can be retrofitted, for models with weighing plate size **A**, height of stand approx. 450 mm, KERN EOB-A01N
- KERN EOB: **Non-slip rubber mat**, W×D×H 945×505×5 mm, KERN EOE-A01
- KERN EOS: **Non-slip rubber mat**, W×D×H 900×550×5 mm, KERN EOS-A01

STANDARD



OPTION



Model	Weighing range [Max] kg	Readout [d] g	Reproducibility g	Linearity g	Net weight approx. kg	Weighing plate	Options	
							DAkkS Calibr. Certificate	DKD KERN
KERN								
EOB 15K5	15	5	5	± 10	4,0	A		963-128
EOB 35K10	35	10	10	± 20	4,0	A		963-128
EOB 60K20	60	20	20	± 40	4,8	A		963-129
EOB 60K20L	60	20	20	± 40	14	B	↓	963-129
EOB 150K50	150	50	50	± 100	4,8	A		963-129
EOB 150K50L	150	50	50	± 100	14	B	↓	963-129
EOB 150K50XL	150	50	50	± 100	19	C		963-129
EOB 300K100A	300	100	100	± 200	4,6	A		963-129
EOB 300K100L	300	100	100	± 200	14	B	↓	963-129
EOB 300K100XL	300	100	100	± 200	19	C		963-129
EOS 150K50XL	150	50	50	± 100	19	D		963-129
EOS 300K100XL	300	100	100	± 200	19	D		963-129

↓ Price reduction

KERN Pictograms

 CAL INT	Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight(motordriven)	 GLP INTERN	GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection	 UNDER	Suspended weighing: Load support with hook on the underside of the balance
 CAL EXT	Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required	 GLP PRINTER	GLP/ISO log: With weight, date and time. Only with KERN printers	 BATT	Battery operation: Ready for battery operation. The battery type is specified for each device
 MEMORY	Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 PCS	Piece counting: Reference quantities selectable. Display can be switched from piece to weight	 ACCU	Rechargeable battery pack: Rechargeable set
 ALIBI	Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	 RECIPE A	Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	 MULTI	Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 RS 232	Data interface RS-232: To connect the balance to a printer, PC or network	 RECIPE B	Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	 230 V	Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available
 RS 485	RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	 RECIPE C	Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition	 230 V	Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
 USB	USB data interface: To connect the balance to a printer, PC or other peripherals	 SUM	Totalising level A: The weights of similar items can be added together and the total can be printed out	 DMS	Weighing principle: Strain gauges Electrical resistor on an elastic deforming body
 BT	Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals	 PERCENT	Percentage determination: Determining the deviation in % from the target value (00 %)	 T-FORK	Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate
 WLAN	WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals	 UNIT	Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details	 FORCE	Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
 SWITCH	Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	 TOL	Weighing with tolerance range: (Check-weighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	 SC TECH	Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision
 DUAL	Interface for second balance: For direct connection of a second balance	 MOVE	Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 M +3 DAYS	Verification possible: The time required for verification is specified in the pictogram
 LAN	Network interface: For connecting the scale to an Ethernet network	 IP	Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.	 DAkkS +3 DAYS	DAkkS calibration possible (DKD): The time required for DAkkS calibration is shown in days in the pictogram
 RC	Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module	 INOX	Stainless steel: The balance is protected against corrosion	 1 DAY	Package shipment: The time required for internal shipping preparations is shown in days in the pictogram
 KCP	KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems			 2 DAYS	Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

Impex Produkter AS
Gamle Drammensvei 107
1363 HØVIK
Tel. 22 32 77 20
info@impex.no
www.impex.no