



All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications

Features

- Thanks to the **many typical laboratory functions**, such as, for example, recipe function, percentage determination, GLP record keeping, combined with the high level of precision, the KERN 572 - 573 is a reliable partner for day-to-day work in the laboratory
- **The robust version**, typical industrial functions, such as piece-counting, vibrationfree weighing and the large weighing ranges also make these balances ideal for all industrial applications, where a high level of precision is required

- **Freely programmable weighing unit**, e.g. display direct in special units such as length of thread g/m, paper weight g/m², or similar
- **The robust aluminium diecast housing** maintains the stability, protects the weighing technology elements and is robust enough to cope with everyday use
- **Ring-shaped draught shield** standard, only for models with weighing plate size **A**, weighing space $\varnothing \times H$ 157×43 mm
- **Loop and hook for underfloor weighing**, standard for models with [d] ≥ 0,01 g
- **Protective working cover** included with delivery

Technical data

- Large backlit LCD display, digit height 18 mm
- Dimensions weighing surface, stainless steel
 - A** \varnothing 106 mm
 - B** \varnothing 150 mm
 - C** W×D 160×200 mm
- Overall dimensions W×D×H 180×310×85 mm
- Permissible ambient temperature 10 °C/40 °C

Accessories

- **Protective working cover**, scope of delivery: 5 items, KERN 572-A02S05
- **Rechargeable battery pack external**, operating time up to 30 h without backlight, charging time approx. 10 h, KERN KS-A01
- **Loop for underfloor weighing**, for models with $d \geq 0,01$ g KERN 572-A03
- **1 Large glass draught shield** with 3 sliding doors for easy access to the items being weighed. Weighing space W×D×H 150×140×130 mm, for models with weighing plate size **A**, KERN 572-A05

STANDARD



OPTION



Model	Weighing range [Max] g	Readout [d] g	Reproducibility g	Linearity g	Weighing plate	Option	
						DAkKS Calibr. Certificate	
KERN						DKD	
						KERN	
572-30	240	0,001	0,001	± 0,003	A	963-127	
572-31	300	0,001	0,002	± 0,005	A	963-127	
572-32	420	0,001	0,002	± 0,005	A	963-127	
573-34	650	0,01	0,01	± 0,03	B	963-127	
572-33	1600	0,01	0,01	± 0,03	B	963-127	
572-35	2400	0,01	0,01	± 0,03	B	963-127	
572-37	3000	0,01	0,02	± 0,05	B	963-127	
572-39	4200	0,01	0,02	± 0,05	B	963-127	
572-45	12000	0,05	0,05	± 0,15	C	963-128	
572-55	20000	0,05	0,1	± 0,25	C	963-128	
573-46	6500	0,1	0,1	± 0,3	C	963-128	
572-43	10000	0,1	0,1	± 0,3	C	963-128	
572-49	16000	0,1	0,1	± 0,3	C	963-128	
572-57	24000	0,1	0,1	± 0,3	C	963-128	

KERN Pictograms

 CAL INT Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)	 GLP INTERN GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection	 UNDER Suspended weighing: Load support with hook on the underside of the balance
 CAL EXT Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required	 GLP PRINTER GLP/ISO log: With weight, date and time. Only with KERN printers	 BATT Battery operation: Ready for battery operation. The battery type is specified for each device
 MEMORY Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 PCS Piece counting: Reference quantities selectable. Display can be switched from piece to weight	 ACCU Rechargeable battery pack: Rechargeable set
 ALIBI Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	 RECIPE A Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	 MULTI Universal mains adapter: with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 RS 232 Data interface RS-232: To connect the balance to a printer, PC or network	 RECIPE B Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	 230 V Mains adapter: 230V/50Hz in standard version for EU. On request GB, USA or AUS version available
 RS 485 RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	 RECIPE C Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition	 230 V Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
 USB USB data interface: To connect the balance to a printer, PC or other peripherals	 SUM Totalising level A: The weights of similar items can be added together and the total can be printed out	 DMS Weighing principle: Strain gauges Electrical resistor on an elastic deforming body
 BT Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals	 PERCENT Percentage determination: Determining the deviation in % from the target value (00 %)	 T-FORK Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate
 WLAN WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals	 UNIT Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details	 FORCE Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
 SWITCH Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	 TOL Weighing with tolerance range: (Check-weighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	 SC TECH Weighing principle: Single cell technology Advanced version of the force compensation principle with the highest level of precision
 DUAL Interface for second balance: For direct connection of a second balance	 MOVE Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	 M +3 DAYS Verification possible: The time required for verification is specified in the pictogram
 LAN Network interface: For connecting the scale to an Ethernet network	 IP Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.	 DAkKS +3 DAYS DAKkS calibration possible (DKD): The time required for DAKkS calibration is shown in days in the pictogram
 RC Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module	 INOX Stainless steel: The balance is protected against corrosion	 1 DAY Package shipment: The time required for internal shipping preparations is shown in days in the pictogram
 KCP KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems		 2 DAYS Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg – 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

Impex Produkter AS
Gamle Drammensvei 107
1363 HØVIK
Tel. 22 32 77 20
info@impex.no
www.impex.no