

CENTER 380/382 Refrigerant Leakage Detector

382 With Air Pump



DC 5V
Jack
(382)



R-134a
R-404A
R-410A
R-407C
R-22
R-32
HFO-1234yf
... more Refrigerants Gas



CENTER 380/382 is a perfect tool for air-condition system maintenance. The operation interface is intuitive with buttons, light bar and sound. The "air sucking system" (382) greatly helps the sensitivity and response time. The "auto-reset" (382) function can help the operator to distinguish the leaking spot among the already spreading refrigerant while maintaining high sensitivity.

FEATURES:

- Air Sucking System for faster response and higher sensitivity.(382)
- Refrigerant Leakage Detector is the perfect tool for maintaining the air-condition or a cooling system with compressor and Refrigerant.
- This unit used newly developed semi-conductor sensor which is extremely sensitive to variety of general used Refrigerant.
- Microprocessor Control with advanced digital signal processing.

SPECIFICATIONS

Heated Semiconductor Gas Sensor.
High-Low Leak Sensitivity Selector.(380)
3 Levels Of Sensitivity.(382)
7 LED Tri-colored Visual Leak Level Indicator.
Variable Intensity Audible Alarm.
Ambient Concentration Reset.
15.5"(40CM) Flexible Stainless Probe.
Detection of R-134a, R-404A, R-410A, R-407C, R22,
R32, HFO-1234yf...Refrigerants Gas.
Sensitivity As Small 6gr/year(380); 3gr/year(382).
Accordance With SAE J1627, CE Design.
Low Battery Indication.
Reference Leak Source Included.
Warm-up Time: 45 Seconds.(382)
Operating Temperature: 0 to 40°C(32 to 104°F)
Size: 21.7 x 6.6 x 5.6 cm
Weight: 400g(with batteries)
Power Source: AA Size Alkaline Batteries x 4.
Battery Life: Approx. 40hrs(380)
AC Adapter: @3.3V 0.5A(382)

STANDARD ACCESSORIES

Model	Battery	Operation Manual	Carrying Case	Leak Check Bottle	AC Adapter
CENTER380	●	●	●	●	
CENTER382	●	●	●	●	Option

